TYCAB AUSTRALIA PTY LTD
A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION

1. PRODUCT CODE LFD23202

2. DESCRIPTION 2 Core Parallel Webbed (Figure 8) 32/.2 (1.0 mm sq). P.A.C.W.
U.V resistant V90HT P.V.C insulated.
Extra Low Voltage Garden Light cable. Not for mains connection.
Oxygen Free copper. RoHS compliant PVC.

3. CONSTRUCTION

3.1 CONDUCTOR: 32 strands of 0.2mm Plain Annealed Copper to AS/NZS 1125 Class 5 drawn from Class 110A copper to AS/NZS 1574.

Max. D.C. resistance at 20C: 26.7 ohms / km

3.2 INSULATION: Coloured U.V Resistant V90HT P.V.C.
Parallel Webbed (Figure 8 configuration).

Nominal Diameter: 2.6 x 5.7 mm
Nominal Wall Thickness: 0.6 mm

3.3 IDENTIFICATION: Printed on insulation and metre-marked

TYCAB GARDEN LIGHTING 1MMSQ 001M >I<

METRE MARK LOW NUMBER ON BOTTOM HIGH NUMBER ON TOP