
TYCAB AUSTRALIA PTY LTD
A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION



1. PRODUCT CODE: **DMC71402**

2. DESCRIPTION: **7 core 14/0.2 Plain Copper Wire (0.4mmsq)**
V75 Insulated Aluminium / Polyester tape screened including a 7/0.2 Tinned drain wire. V75C PVC Sheathed.
AUSTEL approval A93/CA/0122
Extra Low Voltage use, not for mains connection.
Oxygen Free Copper. RoHS Compliant PVC.

3. CONSTRUCTION

3.1 CONDUCTOR: 14 strands of 0.2mm nom. Annealed Copper to AS/NZS1125 drawn from Class 110A copper to AS/NZS1574.

Max. D.C. resistance at 20C: 45.0 ohms / klm

3.2 INSULATION: Coloured P.V.C to AS/NZS3808 type V75.

Nominal Diameter: 1.45 mm
Nominal Wall Thickness: 0.26 mm

3.3 LAYUP: 7 cores twisted.
1. Red
2. Blue
3. Green
4. Yellow
5. White
6. Black
7. Brown

3.4 SCREEN: Aluminium / Polyester tape screen in contact along its length with a 7/.2 TACW drain wire.

3.5 SHEATH: Coloured P.V.C. to AS/NZS3808 type 4V75

Nominal Diameter: 6.2 mm
Nominal Wall Thickness: 0.76 mm

3.6 PRINT: on sheath at intervals not exceeding 2 metres