

Twin Sheath 2 Core Flat (AWC)

V90 PVC insulated

Applications

Trailer Wiring, 12/24VDC Low Voltage Applications e.g. Access Control

Product Specifications

Construction:

Conductor: Plain Annealed Copper to AS/NZS1125

Drawn from Class 110A copper to AS/NZS1574

Insulation: Coloured V90 PVC to AS/NZS 3808

Sheath: Coloured 5V90 PVC to AS/NZS3808

Relevant Standard: AS/NZS3808, AS/NZS1125, & AS/NZS1574.

Core Configuration: 1. Red, 2. Black.



Current Code	New Code	No. of Cores	Nominal Area (mm ²)	Strand No. / Size	Amp Rating @ 30 °c	Electrical Resistance @ 20 °c (0/KM)	Nominal OD
AWC27032	AUTS-2	2	0.5	7/0.32	8	33	3.1 x 4.9
AWC21603	AUTS-3	2	1.13	16/0.3	16	16.5	3.3 x 5.5
AWC22603	AUTS-4	2	1.84	26/0.3	22	10.1	3.8 x 6.3
AWC24103	AUTS-5	2	3.0	41/0.3	29	6.4	4.5 x 7.4
AWC26503	AUTS-6	2	5.0	65/0.3	38	4.1	5.7 x 9.6
AWC296032	AUTB-8	2	7.71	96/0.32	59	2.4	7.1 x 12.5
AWC2168032	AUTB-6	2	13.5	168/0.32	82	1.4	8.8 x 16
AWC2252032	AUTB-4	2	20.26	252/0.32	150	0.9	10.3 x 18.6

Derating Factors for Ambient Temperatures °C

Temperature	30	40	50	60	70
Factor	1	0.9	0.76	0.60	0.45